

RACKS

SINGLE OPEN RACK

OPEN FRAME RACKS ARE DESIGNED FOR A PROFESSIONAL CABLE MANAGEMENT IN PROTECTED DATA CENTER ROOMS. SPECIAL CABLING SECTIONS ON THE LEFT AND RIGHT SIDE PROVIDE A FLEXIBLE AND PROPER CABLE MANAGEMENT.





SINGLE OPEN RACK 42U 60*12

NS-504SOR42U6012

FEATURES

- Easily assemble and disassemble for delivery, low cost.
- Can be bolted directly to floor or use plinth no need castors.
- Maximum access for cable management and equipment maintenance.
- Various optional accessories according to requirements(cable management slot, removable working panel, etc).
- Flexible packing methods allows for convenient stocking and end user delivery.
- Multiple sizes available.
- Customization requests welcome.

COLOR

- Body color:RAL9004(black); RAL7035(grey).  

STANDARD AND MATERIAL

Comply with

- ANSI/EIA; RS-310-D; IEC297-2; DIN41491:PART1; DIN41494:PART7; GB/T3047.2-92 standard.
- 19" international standard, metric system and ETSI standard.

SURFACE TREATMENT

- Degreasing, pickling, phosphating, powder coating.

MATERIAL

- SPCC cold rolled steel.

THICKNESS

- Plinth, front and bottom mounting angle 2.0mm the mounting profiles: 1.5mm.

LOADING WEIGHT

- Static loading: 200KG, Height available from 27U to 42U.

TECHNICAL SPECIFICATION

Model	U	Width	Depth	Height
NS-504SOR27U6012	27	585	120	1331
NS-504SOR32U6012	32	585	120	1553
NS-504SOR37U6012	37	585	120	1775
NS-504SOR42U6012	42	585	120	1998

Remark: Height above the height of the cabinet without wheels

