

RACKS

NETWORK CABINET

A NETWORK CABINET IS A COMBINATION OF HARDWARE STRUCTURES DESIGNED TO ACCOMMODATE TECHNICAL EQUIPMENT INCLUDING (ROUTERS, SWITCHES, HUBS, UPSs, CABLES) AND, OF COURSE, SERVERS.



NETWORK CABINET RACK 42U 60*60

NS-502GL42U6060

FEATURES

- Best sales and famous model floor rack.
- Reliable structure,static loading capacity: 800KGs (Optional castors and plinth).
- Adjustable feet and heavy duty castors are available simultaneously,moving conveniently and fixing reliably.
- Baying together easily,quickly,efficiently and firmly.
- Glass front door with metal panel and rear metal door or high density vented front door and rear doors, meeting the requirements of mechanical protection and ventilation.
- Optional cable entry on top cover and bottom panel. Front,rear door and side panel can be removed facility, the bottom has the function of ventilation and rat-proof.
- Varies optional accessories,reliable quality.
- Optional opening hole and varies specification upon customers' special requirements.
- 7 heights: 22U,24U,27U,32U,37U,42U,47U (Can customize).
- Many depth option: 600/800/900/960/1000/1100/1200mm.
- Flexible packing methods allows for convenient stocking and end user delivery.
- Multiple sizes available.
- Customization requests welcome.

STANDARD AND MATERIAL

Comply with

- ANSI/EIA;RS-310-D;IEC297-2; DIN41491:PART1; DIN41494:PART7; GB/T3047.2-92
- Standard and ETSI standard.(grey).

SURFACE TREATMENT

- degreasing,pickling,phosphoric, powder coating.

TECHNICAL SPECIFICATION

MATERIAL

- SPCC cold rolled steel.

THICKNESS

- Mounting profile 2.0mm;
the others:1.0-1.2mm.

COLOR

- Body color:RAL9004(black);
RAL7035(grey).



Model	U	Width	Depth	Height
NS-502GL22U6060	22	600	600	1080
NS-502GL24U6060	24			1150
NS-502GL27U6060	27			1300
NS-502GL32U6060	32			1525
NS-502GL37U6060	37			1745
NS-502GL42U6060	42			1965
NS-502GL47U6060	47			2190

Remark: height above the height of the cabinet without wheels



FRONT DOOR



REAR DOOR